



**yao
chuan**

堯銓實業有限公司
YAO CHUAN ENTERPRISE CO.,LTD.

FR-888-S

**AUTOMOBILE AIR CONDITION SYSTEM
OVERHAUL MACHINE**

Specification

Compressor: 1 HP

(full airtight rotary type)

Vacuum pump: 1 / 2 HP

(2-section type)

Dosage Scale : 30kg \pm 10g

(with separation device)

Measurement:

H118 \times W61 \times D88 (cm)

Weight: 120 Kg

Liquid storage: 10 Kg

(galvanized iron)

Voltage: 110V / 60Hz

Appliance Freon: R134a or R-12

Appliance site:

1. Automobile A/C workshop

2. Bus maintenance



Features

1. Freon basket is attached with measurement and liquid level ball. The stock of recycle, capacity and fill can be seen clearly.
2. Assembled with Freon recycle window enable to inspect the procession.
3. Once the recycle process is finished, machine will stop, unload,----- automatically. .
4. The equipment high-quality ball valve switch, firm is durable, airtight.
5. Stores the fluid barrel, the oil separator, the heat interchanger completely **all is the galvanized iron material quality**, never rusty, strengthens the recycler's life.
6. Installs three minutes engines off protective device, avoids recycler's engine off immediately opening machine.
7. Easier for pipeline cleaning without removing to save time and labor.
This system is available for dynamic and static cleaning in providing superb effect without agent or any expenses.
8. Air and liquid Freon are recyclable. **Recycle speed: liquid about 1.2Kg/min, Air about 0.65kg/min.**
9. Automatic cool equipment is assembled. It won't damage the compressor even **for long time operation.**

TEL : 886-7-3730278 、 886-7-3632313

URL : www.yao-chuan.com.tw

E-mail : yao@yao-chuan.com.tw